

Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. It is very difficult to determine what are the most popular modern programming languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. There are many approaches to the Software development process. Use of a static code analysis tool can help detect some possible problems. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Programs were mostly entered using punched cards or paper tape. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. It is very difficult to determine what are the most popular modern programming languages. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Many applications use a mix of several languages in their construction and use.