

Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Following a consistent programming style often helps readability. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Many applications use a mix of several languages in their construction and use. There exist a lot of different approaches for each of those tasks. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Programming languages are essential for software development. Code-breaking algorithms have also existed for centuries. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications.