

Unreadable code often leads to bugs, inefficiencies, and duplicated code. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Use of a static code analysis tool can help detect some possible problems. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Programming languages are essential for software development. Different programming languages support different styles of programming (called programming paradigms). Computer programmers are those who write computer software. Many applications use a mix of several languages in their construction and use. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Normally the first step in debugging is to attempt to reproduce the problem. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Computer programmers are those who write computer software. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Techniques like Code refactoring can enhance readability. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Programmable devices have existed for centuries. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages.