

For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). It is usually easier to code in "high-level" languages than in "low-level" ones. Following a consistent programming style often helps readability. There are many approaches to the Software development process. Techniques like Code refactoring can enhance readability. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Integrated development environments (IDEs) aim to integrate all such help. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. There are many approaches to the Software development process. It is very difficult to determine what are the most popular modern programming languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Integrated development environments (IDEs) aim to integrate all such help. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit.