

Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Many applications use a mix of several languages in their construction and use. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Different programming languages support different styles of programming (called programming paradigms). By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Scripting and breakpointing is also part of this process. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Also, specific user environment and usage history can make it difficult to reproduce the problem. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Different programming languages support different styles of programming (called programming paradigms). Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Unreadable code often leads to bugs, inefficiencies, and duplicated code.