

It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. There are many approaches to the Software development process. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Integrated development environments (IDEs) aim to integrate all such help. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Also, specific user environment and usage history can make it difficult to reproduce the problem. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. It is usually easier to code in "high-level" languages than in "low-level" ones. Also, specific user environment and usage history can make it difficult to reproduce the problem. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se.