

He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. Computer programmers are those who write computer software. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Programmable devices have existed for centuries. Also, specific user environment and usage history can make it difficult to reproduce the problem. Programmable devices have existed for centuries. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Different programming languages support different styles of programming (called programming paradigms). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Unreadable code often leads to bugs, inefficiencies, and duplicated code. Use of a static code analysis tool can help detect some possible problems. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Different programming languages support different styles of programming (called programming paradigms). Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. However, readability is more than just programming style. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code.