

The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. However, readability is more than just programming style. Programs were mostly entered using punched cards or paper tape. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Also, specific user environment and usage history can make it difficult to reproduce the problem. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Use of a static code analysis tool can help detect some possible problems. Use of a static code analysis tool can help detect some possible problems. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Different programming languages support different styles of programming (called programming paradigms). Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Following a consistent programming style often helps readability. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Ideally, the programming language best suited for the task at hand will be selected. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers.