

One approach popular for requirements analysis is Use Case analysis. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. It is usually easier to code in "high-level" languages than in "low-level" ones. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Following a consistent programming style often helps readability. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Many applications use a mix of several languages in their construction and use. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Ideally, the programming language best suited for the task at hand will be selected. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Computer programmers are those who write computer software.