

Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Following a consistent programming style often helps readability. Code-breaking algorithms have also existed for centuries. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Different programming languages support different styles of programming (called programming paradigms). Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Following a consistent programming style often helps readability. Programs were mostly entered using punched cards or paper tape. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Integrated development environments (IDEs) aim to integrate all such help. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute.