

The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Scripting and breakpointing is also part of this process. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Ideally, the programming language best suited for the task at hand will be selected. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. It is usually easier to code in "high-level" languages than in "low-level" ones. One approach popular for requirements analysis is Use Case analysis. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Programmable devices have existed for centuries. Normally the first step in debugging is to attempt to reproduce the problem. There exist a lot of different approaches for each of those tasks. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Following a consistent programming style often helps readability. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code.