

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. It is very difficult to determine what are the most popular modern programming languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Normally the first step in debugging is to attempt to reproduce the problem. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Programming languages are essential for software development. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. It is usually easier to code in "high-level" languages than in "low-level" ones. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line.