

Programmable devices have existed for centuries. Code-breaking algorithms have also existed for centuries. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. It is usually easier to code in "high-level" languages than in "low-level" ones. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Unreadable code often leads to bugs, inefficiencies, and duplicated code. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Programs were mostly entered using punched cards or paper tape. Use of a static code analysis tool can help detect some possible problems.