

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Techniques like Code refactoring can enhance readability. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Code-breaking algorithms have also existed for centuries. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Unreadable code often leads to bugs, inefficiencies, and duplicated code. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Programs were mostly entered using punched cards or paper tape. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages.