

The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Also, specific user environment and usage history can make it difficult to reproduce the problem. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Many applications use a mix of several languages in their construction and use. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Following a consistent programming style often helps readability. It affects the aspects of quality above, including portability, usability and most importantly maintainability. One approach popular for requirements analysis is Use Case analysis. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Normally the first step in debugging is to attempt to reproduce the problem. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Code-breaking algorithms have also existed for centuries. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug.