

Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. Ideally, the programming language best suited for the task at hand will be selected. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Whatever the approach to development may be, the final program must satisfy some fundamental properties. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Scripting and breakpointing is also part of this process. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Many applications use a mix of several languages in their construction and use. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. It is very difficult to determine what are the most popular modern programming languages. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability.