

Programmable devices have existed for centuries. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Code-breaking algorithms have also existed for centuries. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Code-breaking algorithms have also existed for centuries. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Techniques like Code refactoring can enhance readability.