

While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Many applications use a mix of several languages in their construction and use. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Ideally, the programming language best suited for the task at hand will be selected. Computer programmers are those who write computer software. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Code-breaking algorithms have also existed for centuries. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Normally the first step in debugging is to attempt to reproduce the problem. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. It is very difficult to determine what are the most popular modern programming languages. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Following a consistent programming style often helps readability. Following a consistent programming style often helps readability.