

Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Different programming languages support different styles of programming (called programming paradigms). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Scripting and breakpointing is also part of this process. Techniques like Code refactoring can enhance readability. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Different programming languages support different styles of programming (called programming paradigms). Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Techniques like Code refactoring can enhance readability. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Many applications use a mix of several languages in their construction and use. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). It affects the aspects of quality above, including portability, usability and most importantly maintainability. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers.