

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. There exist a lot of different approaches for each of those tasks. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Following a consistent programming style often helps readability. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Programs were mostly entered using punched cards or paper tape. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA).