

In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Different programming languages support different styles of programming (called programming paradigms). New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. It affects the aspects of quality above, including portability, usability and most importantly maintainability.