

While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. There are many approaches to the Software development process. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. It is very difficult to determine what are the most popular modern programming languages. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. However, readability is more than just programming style. Many applications use a mix of several languages in their construction and use. Different programming languages support different styles of programming (called programming paradigms). It affects the aspects of quality above, including portability, usability and most importantly maintainability. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. It is very difficult to determine what are the most popular modern programming languages. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Programs were mostly entered using punched cards or paper tape. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory.