

High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Scripting and breakpointing is also part of this process. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Scripting and breakpointing is also part of this process. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Unreadable code often leads to bugs, inefficiencies, and duplicated code. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. There exist a lot of different approaches for each of those tasks. One approach popular for requirements analysis is Use Case analysis. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Code-breaking algorithms have also existed for centuries. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Normally the first step in debugging is to attempt to reproduce the problem.