

This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Following a consistent programming style often helps readability. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Different programming languages support different styles of programming (called programming paradigms). Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Ideally, the programming language best suited for the task at hand will be selected. Computer programmers are those who write computer software. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Different programming languages support different styles of programming (called programming paradigms). Different programming languages support different styles of programming (called programming paradigms). Also, specific user environment and usage history can make it difficult to reproduce the problem. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Use of a static code analysis tool can help detect some possible problems. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA).