

In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. However, readability is more than just programming style. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Their jobs usually involve: Although programming has been presented in the media as a somewhat mathematical subject, some research shows that good programmers have strong skills in natural human languages, and that learning to code is similar to learning a foreign language. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in *A Manuscript on Deciphering Cryptographic Messages*. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. There are many approaches to the Software development process.