

While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Following a consistent programming style often helps readability. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Computer programmers are those who write computer software. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Programmable devices have existed for centuries. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Use of a static code analysis tool can help detect some possible problems. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Programming languages are essential for software development. Normally the first step in debugging is to attempt to reproduce the problem. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly.