

Whatever the approach to development may be, the final program must satisfy some fundamental properties. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. There exist a lot of different approaches for each of those tasks. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Unreadable code often leads to bugs, inefficiencies, and duplicated code. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Ideally, the programming language best suited for the task at hand will be selected. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Programs were mostly entered using punched cards or paper tape. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. However, readability is more than just programming style. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Scripting and breakpointing is also part of this process.