

He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Different programming languages support different styles of programming (called programming paradigms). It is usually easier to code in "high-level" languages than in "low-level" ones. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. It is usually easier to code in "high-level" languages than in "low-level" ones. Different programming languages support different styles of programming (called programming paradigms). However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. However, readability is more than just programming style. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Different programming languages support different styles of programming (called programming paradigms). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. Many applications use a mix of several languages in their construction and use. Use of a static code analysis tool can help detect some possible problems. However, readability is more than just programming style. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Following a consistent programming style often helps readability. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages.