

Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Also, specific user environment and usage history can make it difficult to reproduce the problem. Techniques like Code refactoring can enhance readability. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Code-breaking algorithms have also existed for centuries. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Normally the first step in debugging is to attempt to reproduce the problem. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Many applications use a mix of several languages in their construction and use. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. However, readability is more than just programming style. Computer programmers are those who write computer software. Also, specific user environment and usage history can make it difficult to reproduce the problem. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. One approach popular for requirements analysis is Use Case analysis. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware.