

Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Code-breaking algorithms have also existed for centuries. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Programming languages are essential for software development. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Programming languages are essential for software development. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Following a consistent programming style often helps readability. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. There exist a lot of different approaches for each of those tasks. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. There exist a lot of different approaches for each of those tasks. It is very difficult to determine what are the most popular modern programming languages. Integrated development environments (IDEs) aim to integrate all such help.