

This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Programs were mostly entered using punched cards or paper tape. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Many applications use a mix of several languages in their construction and use. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Computer programmers are those who write computer software. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'.

Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. It affects the aspects of quality above, including portability, usability and most importantly maintainability. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the *Book of Ingenious Devices*. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute.