

He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Programmable devices have existed for centuries. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. It is usually easier to code in "high-level" languages than in "low-level" ones. Code-breaking algorithms have also existed for centuries. One approach popular for requirements analysis is Use Case analysis. Many applications use a mix of several languages in their construction and use. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Many applications use a mix of several languages in their construction and use. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. There exist a lot of different approaches for each of those tasks. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. It is very difficult to determine what are the most popular modern programming languages. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Integrated development environments (IDEs) aim to integrate all such help.