

It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. It is very difficult to determine what are the most popular modern programming languages. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Programs were mostly entered using punched cards or paper tape. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. It affects the aspects of quality above, including portability, usability and most importantly maintainability. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Techniques like Code refactoring can enhance readability. There exist a lot of different approaches for each of those tasks. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Different programming languages support different styles of programming (called programming paradigms). When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. One approach popular for requirements analysis is Use Case analysis. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language.