

Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Allen Downey, in his book *How To Think Like A Computer Scientist*, writes: Many computer languages provide a mechanism to call functions provided by shared libraries. Many applications use a mix of several languages in their construction and use. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Computer programmers are those who write computer software. Programming languages are essential for software development. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Also, specific user environment and usage history can make it difficult to reproduce the problem. Code-breaking algorithms have also existed for centuries. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Computer programmers are those who write computer software. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages.