

FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Use of a static code analysis tool can help detect some possible problems. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Many applications use a mix of several languages in their construction and use. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Ideally, the programming language best suited for the task at hand will be selected. One approach popular for requirements analysis is Use Case analysis. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Unreadable code often leads to bugs, inefficiencies, and duplicated code. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Use of a static code analysis tool can help detect some possible problems. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Ideally, the programming language best suited for the task at hand will be selected. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling).