

One approach popular for requirements analysis is Use Case analysis. Different programming languages support different styles of programming (called programming paradigms). It is very difficult to determine what are the most popular modern programming languages. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Integrated development environments (IDEs) aim to integrate all such help. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. There exist a lot of different approaches for each of those tasks. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Use of a static code analysis tool can help detect some possible problems. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Following a consistent programming style often helps readability.