

There exist a lot of different approaches for each of those tasks. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. It affects the aspects of quality above, including portability, usability and most importantly maintainability. Normally the first step in debugging is to attempt to reproduce the problem. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Different programming languages support different styles of programming (called programming paradigms). There are many approaches to the Software development process. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Programmable devices have existed for centuries. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Computer programmers are those who write computer software. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). Languages form an approximate spectrum from "low-level" to "high-level"; "low-level" languages are typically more machine-oriented and faster to execute, whereas "high-level" languages are more abstract and easier to use but execute less quickly. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. Computer programmers are those who write computer software. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Scripting and breakpointing is also part of this process. Different programming languages support different styles of programming (called programming paradigms). Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation.