

Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. There exist a lot of different approaches for each of those tasks. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Whatever the approach to development may be, the final program must satisfy some fundamental properties. There are many approaches to the Software development process. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Ideally, the programming language best suited for the task at hand will be selected. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. Techniques like Code refactoring can enhance readability. Programmable devices have existed for centuries. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Use of a static code analysis tool can help detect some possible problems. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers.