

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Techniques like Code refactoring can enhance readability. There are many approaches to the Software development process. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. Code-breaking algorithms have also existed for centuries. There are many approaches to the Software development process. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Normally the first step in debugging is to attempt to reproduce the problem. Integrated development environments (IDEs) aim to integrate all such help. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. When debugging the problem in a GUI, the programmer can try to skip some user interaction from the original problem description and check if remaining actions are sufficient for bugs to appear. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Ideally, the programming language best suited for the task at hand will be selected. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. There are many approaches to the Software development process. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process.