

For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Scripting and breakpointing is also part of this process. Code-breaking algorithms have also existed for centuries. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Normally the first step in debugging is to attempt to reproduce the problem. They are the building blocks for all software, from the simplest applications to the most sophisticated ones. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Ideally, the programming language best suited for the task at hand will be selected. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. There exist a lot of different approaches for each of those tasks. Different programming languages support different styles of programming (called programming paradigms). A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. There are many approaches to the Software development process. Programming languages are essential for software development. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. Code-breaking algorithms have also existed for centuries. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams.