

Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Expert programmers are familiar with a variety of well-established algorithms and their respective complexities and use this knowledge to choose algorithms that are best suited to the circumstances. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Scripting and breakpointing is also part of this process. Different programming languages support different styles of programming (called programming paradigms). In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Code-breaking algorithms have also existed for centuries. Integrated development environments (IDEs) aim to integrate all such help. It is very difficult to determine what are the most popular modern programming languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Techniques like Code refactoring can enhance readability. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Different programming languages support different styles of programming (called programming paradigms). Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. Integrated development environments (IDEs) aim to integrate all such help.