

Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The academic field and the engineering practice of computer programming are both largely concerned with discovering and implementing the most efficient algorithms for a given class of problems. Methods of measuring programming language popularity include: counting the number of job advertisements that mention the language, the number of books sold and courses teaching the language (this overestimates the importance of newer languages), and estimates of the number of existing lines of code written in the language (this underestimates the number of users of business languages such as COBOL). After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Different programming languages support different styles of programming (called programming paradigms). The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. Normally the first step in debugging is to attempt to reproduce the problem. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. There are many approaches to the Software development process. Ideally, the programming language best suited for the task at hand will be selected. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. There exist a lot of different approaches for each of those tasks. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. One approach popular for requirements analysis is Use Case analysis. In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them.