

This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. As early as the 9th century, a programmable music sequencer was invented by the Persian Banu Musa brothers, who described an automated mechanical flute player in the Book of Ingenious Devices. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Computer programmers are those who write computer software. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. Use of a static code analysis tool can help detect some possible problems. Whatever the approach to development may be, the final program must satisfy some fundamental properties. However, readability is more than just programming style. Programs were mostly entered using punched cards or paper tape. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. There exist a lot of different approaches for each of those tasks. It is usually easier to code in "high-level" languages than in "low-level" ones. Assembly languages were soon developed that let the programmer specify instruction in a text format (e.g., ADD X, TOTAL), with abbreviations for each operation code and meaningful names for specifying addresses. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). One approach popular for requirements analysis is Use Case analysis. Computer programmers are those who write computer software.