

There are many approaches to the Software development process. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Use of a static code analysis tool can help detect some possible problems. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Programmable devices have existed for centuries. However, readability is more than just programming style. It affects the aspects of quality above, including portability, usability and most importantly maintainability. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Following a consistent programming style often helps readability. One approach popular for requirements analysis is Use Case analysis. Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. Sometimes software development is known as software engineering, especially when it employs formal methods or follows an engineering design process. Some languages are very popular for particular kinds of applications, while some languages are regularly used to write many different kinds of applications. In the 1880s, Herman Hollerith invented the concept of storing data in machine-readable form. There are many approaches to the Software development process. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Programmable devices have existed for centuries. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Normally the first step in debugging is to attempt to reproduce the problem. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams.