

In 1801, the Jacquard loom could produce entirely different weaves by changing the "program" – a series of pasteboard cards with holes punched in them. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. There are many approaches to the Software development process. However, readability is more than just programming style. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Normally the first step in debugging is to attempt to reproduce the problem. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. However, readability is more than just programming style. Code-breaking algorithms have also existed for centuries. Following a consistent programming style often helps readability. Many applications use a mix of several languages in their construction and use. Different programming languages support different styles of programming (called programming paradigms). These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. It is very difficult to determine what are the most popular modern programming languages. Programmers typically use high-level programming languages that are more easily intelligible to humans than machine code, which is directly executed by the central processing unit. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. Computer programmers are those who write computer software. It is usually easier to code in "high-level" languages than in "low-level" ones. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. Use of a static code analysis tool can help detect some possible problems. In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine.