

The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. There are many approaches to the Software development process. This can be a non-trivial task, for example as with parallel processes or some unusual software bugs. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Whatever the approach to development may be, the final program must satisfy some fundamental properties. Some text editors such as Emacs allow GDB to be invoked through them, to provide a visual environment. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. By the late 1960s, data storage devices and computer terminals became inexpensive enough that programs could be created by typing directly into the computers. For example, COBOL is still strong in corporate data centers often on large mainframe computers, Fortran in engineering applications, scripting languages in Web development, and C in embedded software. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Integrated development environments (IDEs) aim to integrate all such help. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Many applications use a mix of several languages in their construction and use. Debugging is a very important task in the software development process since having defects in a program can have significant consequences for its users. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. However, because an assembly language is little more than a different notation for a machine language, two machines with different instruction sets also have different assembly languages. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. Scripting and breakpointing is also part of this process. Integrated development environments (IDEs) aim to integrate all such help.