

After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. Auxiliary tasks accompanying and related to programming include analyzing requirements, testing, debugging (investigating and fixing problems), implementation of build systems, and management of derived artifacts, such as programs' machine code. For this purpose, algorithms are classified into orders using so-called Big O notation, which expresses resource use, such as execution time or memory consumption, in terms of the size of an input. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Text editors were also developed that allowed changes and corrections to be made much more easily than with punched cards. The first compiler related tool, the A-0 System, was developed in 1952 by Grace Hopper, who also coined the term 'compiler'. Implementation techniques include imperative languages (object-oriented or procedural), functional languages, and logic languages. Also, specific user environment and usage history can make it difficult to reproduce the problem. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. However, readability is more than just programming style. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. A similar technique used for database design is Entity-Relationship Modeling (ER Modeling). Normally the first step in debugging is to attempt to reproduce the problem. After the bug is reproduced, the input of the program may need to be simplified to make it easier to debug. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Many applications use a mix of several languages in their construction and use. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. There are many approaches to the Software development process. However, readability is more than just programming style.