

For example, when a bug in a compiler can make it crash when parsing some large source file, a simplification of the test case that results in only few lines from the original source file can be sufficient to reproduce the same crash. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. The first step in most formal software development processes is requirements analysis, followed by testing to determine value modeling, implementation, and failure elimination (debugging). High-level languages made the process of developing a program simpler and more understandable, and less bound to the underlying hardware. Many applications use a mix of several languages in their construction and use. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Provided the functions in a library follow the appropriate run-time conventions (e.g., method of passing arguments), then these functions may be written in any other language. Integrated development environments (IDEs) aim to integrate all such help. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. It involves designing and implementing algorithms, step-by-step specifications of procedures, by writing code in one or more programming languages. The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. There are many approaches to the Software development process. One approach popular for requirements analysis is Use Case analysis.

Trial-and-error/divide-and-conquer is needed: the programmer will try to remove some parts of the original test case and check if the problem still exists. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. However, Charles Babbage had already written his first program for the Analytical Engine in 1837. There are many approaches to the Software development process. Use of a static code analysis tool can help detect some possible problems. While these are sometimes considered programming, often the term software development is used for this larger overall process – with the terms programming, implementation, and coding reserved for the writing and editing of code per se. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Proficient programming usually requires expertise in several different subjects, including knowledge of the application domain, details of programming languages and generic code libraries, specialized algorithms, and formal logic. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code.