

The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. However, readability is more than just programming style. Use of a static code analysis tool can help detect some possible problems. Unreadable code often leads to bugs, inefficiencies, and duplicated code. However, with the concept of the stored-program computer introduced in 1949, both programs and data were stored and manipulated in the same way in computer memory. Programming languages are essential for software development. Scripting and breakpointing is also part of this process. Computer programming or coding is the composition of sequences of instructions, called programs, that computers can follow to perform tasks. Programmable devices have existed for centuries. Many programmers use forms of Agile software development where the various stages of formal software development are more integrated together into short cycles that take a few weeks rather than years. The Unified Modeling Language (UML) is a notation used for both the OOAD and MDA. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). Programs were mostly entered using punched cards or paper tape. There are many approaches to the Software development process. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. FORTRAN, the first widely used high-level language to have a functional implementation, came out in 1957, and many other languages were soon developed—in particular, COBOL aimed at commercial data processing, and Lisp for computer research. Debugging is often done with IDEs. Standalone debuggers like GDB are also used, and these often provide less of a visual environment, usually using a command line. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. Unreadable code often leads to bugs, inefficiencies, and duplicated code. There exist a lot of different approaches for each of those tasks. Compilers harnessed the power of computers to make programming easier by allowing programmers to specify calculations by entering a formula using infix notation. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. Trade-offs from this ideal involve finding enough programmers who know the language to build a team, the availability of compilers for that language, and the efficiency with which programs written in a given language execute. Various visual programming languages have also been developed with the intent to resolve readability concerns by adopting non-traditional approaches to code structure and display.