

However, readability is more than just programming style. Later a control panel (plug board) added to his 1906 Type I Tabulator allowed it to be programmed for different jobs, and by the late 1940s, unit record equipment such as the IBM 602 and IBM 604, were programmed by control panels in a similar way, as were the first electronic computers. Ideally, the programming language best suited for the task at hand will be selected. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. Popular modeling techniques include Object-Oriented Analysis and Design (OOAD) and Model-Driven Architecture (MDA). In 1206, the Arab engineer Al-Jazari invented a programmable drum machine where a musical mechanical automaton could be made to play different rhythms and drum patterns, via pegs and cams. Many factors, having little or nothing to do with the ability of the computer to efficiently compile and execute the code, contribute to readability. These compiled languages allow the programmer to write programs in terms that are syntactically richer, and more capable of abstracting the code, making it easy to target varying machine instruction sets via compilation declarations and heuristics. Some languages are more prone to some kinds of faults because their specification does not require compilers to perform as much checking as other languages. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). Code-breaking algorithms have also existed for centuries. Readability is important because programmers spend the majority of their time reading, trying to understand, reusing and modifying existing source code, rather than writing new source code. A study found that a few simple readability transformations made code shorter and drastically reduced the time to understand it. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. Programs were mostly entered using punched cards or paper tape. Some of these factors include: The presentation aspects of this (such as indents, line breaks, color highlighting, and so on) are often handled by the source code editor, but the content aspects reflect the programmer's talent and skills. The following properties are among the most important: In computer programming, readability refers to the ease with which a human reader can comprehend the purpose, control flow, and operation of source code. He gave the first description of cryptanalysis by frequency analysis, the earliest code-breaking algorithm. In the 9th century, the Arab mathematician Al-Kindi described a cryptographic algorithm for deciphering encrypted code, in A Manuscript on Deciphering Cryptographic Messages. Machine code was the language of early programs, written in the instruction set of the particular machine, often in binary notation. New languages are generally designed around the syntax of a prior language with new functionality added, (for example C++ adds object-orientation to C, and Java adds memory management and bytecode to C++, but as a result, loses efficiency and the ability for low-level manipulation). The choice of language used is subject to many considerations, such as company policy, suitability to task, availability of third-party packages, or individual preference. The first computer program is generally dated to 1843, when mathematician Ada Lovelace published an algorithm to calculate a sequence of Bernoulli numbers, intended to be carried out by Charles Babbage's Analytical Engine. Techniques like Code refactoring can enhance readability. Normally the first step in debugging is to attempt to reproduce the problem.